

SAFETY DATA SHEET

1. Identification

1. Identification						
Product identifier	Liquid Wrench Hydraulic Jack Oil					
Other means of identification						
SDS number	M3312					
Part No.	M3332, M3312					
Tariff code	2710.19.3040					
Recommended use	Hydraulic Fluid					
Recommended restrictions	Recommended restrictions None known.					
Manufacturer/Importer/Supplier Manufacturer	/Distributor information					
Company name Address	Blumenthal Brands Integrated, LLC 600 Radiator Road Indian Trail, NC 28079					
Telephone	Customer Service/ (704) 821-7643 Technical					
Website	www.solvewithB.com					
E-mail	sds@solvewithB.com INFOTRAC (United States) (800) 535-5053					
Emergency phone number	INFOTRAC (United States) (800) 535-5053 INFOTRAC (International) (352) 323-3500					
2. Hazard(s) identification	n					
Physical hazards	Not classified.					
Health hazards	Reproductive toxicity (fertility, the unborn Category 1A child)					
Environmental hazards	Not classified.					
OSHA defined hazards	Not classified.					
Label elements						
Signal word	Danger					
Hazard statement	May be harmful if swallowed and enters airways. May damage fertility. May damage the unborn child.					
Precautionary statement						
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.					
Response	If exposed or concerned: Get medical advice/attention.					
Storage	Store locked up.					
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.					
Hazard(s) not otherwise classified (HNOC)	None known.					

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients

Supplemental information

Chemical name	Common name and synonyms	CAS number	%
Mineral Oil		Mixture	90 - 100
Calcium Alkaryl Sulfonate		Proprietary	< 0.5
Calcium Long-chain Alkylphena Sulfide	te	Proprietary	< 0.5
Long-chain Alkenyl Succinimide)	Proprietary	< 0.5
Zinc dialkyldithiophosphate		68649-42-3	< 0.5
Other components below report			< 1
*Designates that a specific chemic	al identity and/or percentage of composition ha	as been withheld as a trade sec	cret.
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if symptor	ns develop or persist.	
Skin contact	Wash off with soap and water. Get medical a	attention if irritation develops an	d persists.
Eye contact	Rinse with water. Get medical attention if irri	• •	
Ingestion	Call a physician or poison control center imm vomiting. If vomiting occurs, keep head low s		
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause tempora	ry irritation.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and tre Symptoms may be delayed.	eat symptomatically. Keep victir	n under observation.
General information	IF exposed or concerned: Get medical advic (show the label where possible). Ensure that involved, and take precautions to protect the attendance.	medical personnel are aware of	of the material(s)
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Car	bon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as the	his will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may b	be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full p	protective clothing must be wor	n in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do	so without risk.	
Specific methods	Use standard firefighting procedures and cor	nsider the hazards of other invo	lved materials.
General fire hazards	No unusual fire or explosion hazards noted.		
6. Accidental release mea	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep per appropriate protective equipment and clothin authorities should be advised if significant sp see section 8 of the SDS.	ig during clean-up. Ensure ade	quate ventilation. Local
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this possible. Absorb in vermiculite, dry sand or e recovery, flush area with water.	is without risk. Dike the spilled earth and place into containers.	material, where this is Following product
	Small Spills: Wipe up with absorbent materia remove residual contamination.	al (e.g. cloth, fleece). Clean surf	ace thoroughly to
	Never return spills to original containers for r		section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses o	r onto the ground.	
7. Handling and storage			
Precautions for safe handling	Obtain special instructions before use. Do no and understood. Avoid prolonged exposure. this product. Should be handled in closed sy appropriate personal protective equipment.	Pregnant or breastfeeding won stems, if possible. Provide ade	nen must not handle quate ventilation. Wear

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
CADMIUM (CAS 7440-43-9)	TWA	0.005 mg/m3	
ETHYLENE OXIDE (CAS 75-21-8)	STEL	5 ppm	
	TWA	1 ppm	
LEAD (CAS 7439-92-1)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air (Contaminants (29 CFR 1910.1	000)	
Components	Туре	Value	
1,4-dioxane (CAS 123-91-1)	PEL	360 mg/m3	
		100 ppm	
PROPYLENE OXIDE (CAS	PEL	240 mg/m3	
75-56-9)		100 ppm	
US. OSHA Table Z-2 (29 CFR 1910.	1000)		
Components	Туре	Value	Form
CADMIUM (CAS 7440-43-9)	Ceiling	0.6 mg/m3	Dust.
		0.3 mg/m3	Fume.
	TWA	0.2 mg/m3	Dust.
		0.1 mg/m3	Fume.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
US. ACGIH Threshold Limit Values Components 1,4-dioxane (CAS 123-91-1)		Value 20 ppm	Form
Components	Туре		Form
Components 1,4-dioxane (CAS 123-91-1)	Type TWA	20 ppm	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS	Type TWA	20 ppm 0.01 mg/m3	
Components 1,4-dioxane (CAS 123-91-1)	Type TWA TWA	20 ppm 0.01 mg/m3 0.002 mg/m3	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8)	Type TWA TWA TWA	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm	Form Respirable fraction.
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9) US. NIOSH: Pocket Guide to Chemi	Type TWA TWA TWA TWA TWA TWA	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm 0.05 mg/m3 2 ppm	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9) US. NIOSH: Pocket Guide to Chemic Components	Type TWA TWA TWA TWA TWA	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm 0.05 mg/m3	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9) US. NIOSH: Pocket Guide to Chemi	Type TWA TWA TWA TWA TWA TWA	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm 0.05 mg/m3 2 ppm	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9) US. NIOSH: Pocket Guide to Chemic Components	Type TWA TWA TWA TWA TWA TWA TWA TWA	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm 0.05 mg/m3 2 ppm Value	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9) US. NIOSH: Pocket Guide to Chemic Components	Type TWA TWA TWA TWA TWA TWA TWA TWA	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm 0.05 mg/m3 2 ppm Value 3.6 mg/m3	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9) US. NIOSH: Pocket Guide to Chemi Components 1,4-dioxane (CAS 123-91-1) ETHYLENE OXIDE (CAS	Type TWA TWA TWA TWA TWA twA twA Ceiling	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm 0.05 mg/m3 2 ppm Value 3.6 mg/m3 1 ppm	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9) US. NIOSH: Pocket Guide to Chemi Components 1,4-dioxane (CAS 123-91-1) ETHYLENE OXIDE (CAS	Type TWA TWA TWA TWA TWA twA twA Ceiling	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm 0.05 mg/m3 2 ppm Value 3.6 mg/m3 1 ppm 9 mg/m3	
Components 1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9) US. NIOSH: Pocket Guide to Chemi Components 1,4-dioxane (CAS 123-91-1) ETHYLENE OXIDE (CAS	Type TWA TWA TWA TWA TWA twA Ceiling Ceiling	20 ppm 0.01 mg/m3 0.002 mg/m3 1 ppm 0.05 mg/m3 2 ppm Value 3.6 mg/m3 1 ppm 9 mg/m3 5 ppm	

Components	Value	Determinant	Specimen	Sampling Time
CADMIUM (CAS 7440-43-	9)5 µg/g	Cadmium	Creatinine in urine	*
	5 µg/l	Cadmium	Blood	*
LEAD (CAS 7439-92-1)	200 µg/l	Lead	Blood	*
* - For sampling details, pl	ease see the sourc	e document.		
xposure guidelines				
US - California OELs: Sk	in designation			
1,4-dioxane (CAS 123			e absorbed throug	gh the skin.
US - Minnesota Haz Subs	s: Skin designatio	n applies		
1,4-dioxane (CAS 123	,	Skin d	esignation applies	5.
US - Tennessee OELs: S	•			
1,4-dioxane (CAS 123 US ACGIH Threshold Lin	,		e absorbed throug	gh the skin.
1,4-dioxane (CAS 123 US. OSHA Table Z-1 Lim i	,		e absorbed throuç 00)	gh the skin.
1,4-dioxane (CAS 123	3-91-1)	Can be	e absorbed throug	gh the skin.
Appropriate engineering controls	should be ma or other engin	tched to conditions. If ap eering controls to mainta	plicable, use proc ain airborne levels	our) should be used. Ventilation rates sess enclosures, local exhaust ventilation, below recommended exposure limits. If sorne levels to an acceptable level.
ndividual protection measur	es, such as perso	nal protective equipme	nt	
Eye/face protection	Chemical resp settings only.	pirator with organic vapo	r cartridge and ful	I facepiece. Applicable for industrial
Skin protection				
Hand protection	Wear appropr	iate chemical resistant g	loves. Applicable	for industrial settings only.
Other	Use of an imp	ervious apron is recomm	nended. Applicabl	e for industrial settings only.
Respiratory protection				I facepiece. Chemical respirator with nits are exceeded. Applicable for industrial
Thermal hazards	Wear appropr	iate thermal protective c	lothing, when nec	essary.
General hygiene considerations	measures, su	ch as washing after hand	lling the material	s observe good personal hygiene and before eating, drinking, and/or equipment to remove contaminants.

Liquid Clear. Appearance Liquid. **Physical state** Form Liquid. Color Colorless. Mild Petroleum Odor Odor threshold Not available. Not available. pН Not available. Melting point/freezing point Initial boiling point and boiling Not available. range Flash point > 410.0 °F (> 210.0 °C) **Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Not available. Flammability limit - lower

```
(%)
```

Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.013 torr @ 25C
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	6.9 cSt
Viscosity temperature	212 °F (100 °C)
Other information	
Density	0.9 g/ml @ 15.6 C
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Kinematic viscosity	31.7 mm²/s
Kinematic viscosity temperature	104 °F (40 °C)
Oxidizing properties	Not oxidizing.
Percent volatile	0.3 % estimated
Pour point	-40 °F (-40 °C)
Specific gravity	0.9
VOC	0.35 % estimated
10. Stability and reactivity	

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardous
reactionsNo dangerous reaction known under conditions of normal use.Conditions to avoidKeep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with
incompatible materials.Incompatible materialsStrong oxidizing agents.Hazardous decomposition
productsNo hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.		
Skin contact	No adverse effects due to skin contact are expected.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.		
Information on toxicological effects			

Acute toxicity

Components	Species	Test Results	
1,4-dioxane (CAS 123-91-1)			
Acute			
Dermal			
LD50	Rabbit	7600 mg/kg	
Inhalation			
LC50	Rat	46 mg/l, 2 Hours	
Oral			
LD50	Rat	5150 mg/kg	
CADMIUM (CAS 7440-43-9)			
<u>Acute</u>			
Oral			
LD50	Rat	63 - 259 mg/kg	
ETHYLENE OXIDE (CAS 75-21-8	3)		
Acute			
Inhalation	Dat		
LC50	Rat	1450 ppm, 4 Hours	
Oral	Det	70	
LD50	Rat	72 mg/kg	
LEAD (CAS 7439-92-1)			
<u>Acute</u>			
Dermal LD50	Rat	> 2000 mg/kg 24 Hours	
	Rai	> 2000 mg/kg, 24 Hours	
Inhalation LC50	Rat	> 5.05 mg/l, 4 Hours	
	Rai	> 5.05 High, 4 Hours	
Oral LD50	Rat	> 2000 mg/kg	
		> 2000 mg/kg	
PROPYLENE OXIDE (CAS 75-56	9-9)		
<u>Acute</u> Dermal			
LD50	Rabbit	950 - 1250 mg/kg, 4 Hours	
Inhalation	Rabbit	300 - 1200 mg/kg, 4 hours	
LC50	Mouse	1740 ppm, 4 Hours	
	Wouse		
Oral LD50	Rat	380 mg/kg	
Skin corrosion/irritation	-	nay cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes	may cause temporary irritation.	
Respiratory or skin sensitizatio	n		
ACGIH sensitization			
PROPYLENE OXIDE (C	AS 75-56-9)	Dermal sensitization	
Respiratory sensitization	Not a respiratory sensitiz		
Skin sensitization		ted to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Not classifiable as to car	cinogenicity to humans.	
IARC Monographs. Overall	Evaluation of Carcinogen	icity	
1,4-dioxane (CAS 123-9 CADMIUM (CAS 7440-4 ETHYLENE OXIDE (CAS LEAD (CAS 7439-92-1) PROPYLENE OXIDE (C	1-1) 3-9) S 75-21-8)	2B Possibly carcinogenic to humans. 1 Carcinogenic to humans. 1 Carcinogenic to humans. 2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans.	

OSHA Specifically Regulate	ad Substances	(20 CEP 1010 10	001 1052)	
CADMIUM (CAS 7440-4		(29 CFK 1910.10	Cancer	
ETHYLENE OXIDE (CA	,		Cancer	
US. National Toxicology Pr		eport on Carcine	ogens	
1,4-dioxane (CAS 123-9 CADMIUM (CAS 7440-4 ETHYLENE OXIDE (CA	3-9)		Reasonably Anticipated t Known To Be Human Ca Known To Be Human Ca	
LEAD (CAS 7439-92-1) PROPYLENE OXIDE (C	,		Reasonably Anticipated t	to be a Human Carcinogen. to be a Human Carcinogen.
Reproductive toxicity		fertility. May dam	hage the unborn child.	o bo a Haman Carollogon.
Specific target organ toxicity -	Not classified			
single exposure				
Specific target organ toxicity - repeated exposure	Not classified			
Aspiration hazard	Not an aspira	tion hazard.		
Chronic effects	Prolonged inh	nalation may be h	armful.	
12. Ecological informatio	n			
Ecotoxicity				us. However, this does not exclude the I or damaging effect on the environment.
Components		Species		Test Results
1,4-dioxane (CAS 123-91-1)				
Aquatic				
Fish	LC50	Inland silversid	e (Menidia beryllina)	6700 mg/l, 96 hours
CADMIUM (CAS 7440-43-9)	CADMIUM (CAS 7440-43-9)			
Aquatic				
Crustacea	EC50	Water flea (Da	phnia magna)	0.0491 mg/l, 48 hours
Fish	LC50	Rainbow trout, (Oncorhynchus	donaldson trout s mykiss)	0.0024 - 0.0029 mg/l, 96 hours
ETHYLENE OXIDE (CAS 75-	-21-8)			
Aquatic				
Fish	LC50	Fathead minno	w (Pimephales promelas)	73 - 96 mg/l, 96 hours
LEAD (CAS 7439-92-1) Aquatic				
Fish	LC50	Rainbow trout, (Oncorhynchus	donaldson trout s mykiss)	1.17 mg/l, 96 hours
Persistence and degradability	No data is ava	ailable on the de	gradability of any ingredier	nts in the mixture.
Bioaccumulative potential				
Partition coefficient n-octar	nol / water (log	Kow)	-0.27	
ETHYLENE OXIDE			-0.3	
PROPYLENE OXIDE			0.03	
Mobility in soil	No data availa	able.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
13. Disposal consideration	ons			
Disposal instructions	material unde	r controlled cond		ensed waste disposal site. Incinerate the erator. Dispose of contents/container in lations.
Local disposal regulations		-	-	
Hazardous waste code	Dispose in accordance with all applicable regulations. D006: Waste Cadmium D008: Waste Lead The waste code should be assigned in discussion between the user, the producer and the waste			
	disposal com	sany.		

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
14. Transport information	

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Ex

Not regulated.

Export Notification	(40 CER 707 Subr	nt D)	
	(+• • • • • • • • • • • • • • • • • • •		

CERCLA Hazardous Substance List (40 CFR 302.4)

CERCEA Hazardous Substance List (40 CFR 302.4)	
1,4-dioxane (CAS 123-91-1)	Listed.
CADMIUM (CAS 7440-43-9)	Listed.
ETHYLENE OXIDE (CAS 75-21-8)	Listed.
LEAD (CAS 7439-92-1)	Listed.
PROPYLENE OXIDE (CAS 75-56-9)	Listed.
Zinc dialkyldithiophosphate (CAS 68649-42-3)	Listed.
SARA 304 Emergency release notification	
ETHYLENE OXIDE (CAS 75-21-8)	10 LBS
PROPYLENE OXIDE (CAS 75-56-9)	100 LBS
OSHA Specifically Regulated Substances (29 CFR 1910.1	1001-1052)
CADMIUM (CAS 7440-43-9)	Cancer
ETHYLENE OXIDE (CAS 75-21-8)	Cancer
LEAD (CAS 7439-92-1)	Reproductive toxicity
CADMÌUM (CAS 7440-43-9)	Lung
ETHYLENE OXIDE (CAS 75-21-8)	Reproductive toxicity
LEAD (CAS 7439-92-1)	Central nervous system
CADMIUM (CAS 7440-43-9)	Kidney
ETHYLENE OXIDE (CAS 75-21-8)	Mutagenicity
LEAD (CAS 7439-92-1)	Kidney
CADMIUM (CAS 7440-43-9)	Acute toxicity
ETHYLENE OXIDE (CAS 75-21-8)	Central nervous system
LEAD (CAS 7439-92-1)	Blood
ETHYLENE OXIDE (CAS 75-21-8)	Skin sensitization
LEAD (CAS 7439-92-1)	Acute toxicity
ETHYLENE OXIDE (CAS 75-21-8)	Skin irritation
	Eye irritation
	respiratory tract irritation
	Acute toxicity

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
ETHYLENE OXIDE PROPYLENE OXIDE	75-21-8 75-56-9	10 100	1000 10000		

Flammability

SARA 311/312 Hazardous No (Exempt) chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,4-dioxane	123-91-1	< 0.2	
CADMIUM	7440-43-9	< 0.2	
ETHYLENE OXIDE	75-21-8	< 0.2	
LEAD	7439-92-1	< 0.2	
PROPYLENE OXIDE	75-56-9	< 0.2	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,4-dioxane (CAS 123-91-1) CADMIUM (CAS 7440-43-9) ETHYLENE OXIDE (CAS 75-21-8) LEAD (CAS 7439-92-1) PROPYLENE OXIDE (CAS 75-56-9)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

ETHYLENE OXIDE (CAS 75-21-8) PROPYLENE OXIDE (CAS 75-56-9)

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHYLENE OXIDE (CAS 75-21-8)	Other Flavoring Substances with OSHA PEL's
------------------------------	--

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylene Oxide, which are known to the State of California to cause cancer, and Lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

California Proposition	05 - CKT. LISTEU Uate/Carcint	genic substance	
1,4-dioxane (CAS 1	23-91-1)	Listed: January 1, 1988	
CADMIUM (CAS 74	40-43-9)	Listed: October 1, 1987	
ETHYLENE OXIDE	(CAS 75-21-8)	Listed: July 1, 1987	
LEAD (CAS 7439-92		Listed: October 1, 1992	
PROPYLENE OXIDE (CAS 75-56-9)		Listed: October 1, 1988	
California Proposition	65 - CRT: Listed date/Develo	omental toxin	
CADMIUM (CAS 74	40-43-9)	Listed: May 1, 1997	
Ethylene Glycol (CA	S 107-21-1)	Listed: June 19, 2015	
ETHYLENE OXIDE	(CAS 75-21-8)	Listed: August 7, 2009	
LEAD (CAS 7439-92	2-1)	Listed: February 27, 1987	
California Proposition	65 - CRT: Listed date/Female	reproductive toxin	
ETHYLENE OXIDE	(CAS 75-21-8)	Listed: February 27, 1987	
LEAD (CAS 7439-92	2-1)	Listed: February 27, 1987	
California Proposition	65 - CRT: Listed date/Male re	productive toxin	
CADMIUM (CAS 74	40-43-9)	Listed: May 1, 1997	
ETHYLENE OXIDE		Listed: August 7, 2009	
LEAD (CAS 7439-92-1)		Listed: February 27, 1987	
US. California. Candida	ate Chemicals List. Safer Con	sumer Products Regulations (Cal. Code I	Regs, tit. 22, 69502.3,
subd. (a))			-
1,4-dioxane (CAS 1	23-91-1)		
CADMIUM (CAS 74	,		
ETHYLENE OXIDE	(CAS 75-21-8)		
LEAD (CAS 7439-92	2-1)		
PROPYLENE OXID	E (CAS 75-56-9)		
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Cher	nical Substances (AICS)	No
Canada	Domestic Substances List (I		No
Canada	Non-Domestic Substances L	,	No
Canada			

Country(s) or region	Inventory name On inventory	(yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-01-2015
Revision date	03-26-2020
Version #	04
HMIS® ratings	Health: 2 Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 0 Instability: 0
NFPA ratings	200
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Physical & Chemical Properties: Multiple Properties