

Parts Plus® SAE 0W-20 Synthetic Motor Oil

Revision Date: 02/26/2020 Version: 4.0 Print Date: 03/17/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name Parts Plus® SAE 0W-20

Synthetic Motor Oil

Product code 885002

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

Details of the supplier of the safety data Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654)

sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509

United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) 1-800-TEAMVAL (1-800-832-6825)

Product Information 1-800-TEAMVAL (1-800-832-6825)

Regulatory Information Number

SDS@valvoline.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards which do not result in classification

No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

nazarada componento					
Chemical name	CAS-No.	Classification	Concentration (%)		
PETROLEUM DISTILLATES	64742-54-7	Asp. Tox. 1; H304	>= 50.00 - < 70.00		

Valvoline...

SAFETY DATA SHEET

Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

PETROLEUM DISTILLATES	64742-54-7	Not a hazardous substance or mixture.	>= 1.00 - < 10.00
Branched alkylphenol and Calcium branched alkylphenol	74499-35-7	Skin Corr/Irr 2; H315 Eye Corr/Irr 2A; H319 Repr. 1B; H360F Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.025 - < 0.10

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Specific extinguishing

methods

: Standard procedure for chemical fires.

Product is compatible with standard fire-fighting agents.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM)	64742-65-0	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		TWA	5 mg/m3	CR OEL
		L-8/40	0.2 mg/m3	VE OEL
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		L-8/40	0.2 mg/m3	VE OEL
PETROLEUM DISTILLATES	64741-89-5	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

STEL (Mist)	10 mg/m3 Mist	PE OEL
L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
LB (Mist)	10 mg/m3 Mist	VE OEL
CPT (Mist)	5 mg/m3 Mist	PA OEL
CCT (Mist)	10 mg/m3 Mist	PA OEL
TWA	5 mg/m3	CR OEL

Engineering measures : General room ventilation should be adequate for normal

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Safety shoes

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 220 °C



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.843 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 45.4 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Valvoline,

Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

PETROLEUM DISTILLATES:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

Branched alkylphenol and Calcium branched alkylphenol:

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

PETROLEUM DISTILLATES:



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

Result: No eye irritation

PETROLEUM DISTILLATES:

Result: No eye irritation

Branched alkylphenol and Calcium branched alkylphenol:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

Components:

Branched alkylphenol and Calcium branched alkylphenol:

Reproductive toxicity - : Clear evidence of adverse effects on sexual function and

Assessment fertility, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

PETROLEUM DISTILLATES:

No aspiration toxicity classification



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Further information

The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 30.0798 %

Components:

PETROLEUM DISTILLATES:

: LL50 (Fish): > 100 mg/l Toxicity to fish

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

PETROLEUM DISTILLATES:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

Branched alkylphenol and Calcium branched alkylphenol:

Ecotoxicology Assessment

Short-term (acute) aquatic : Very toxic to aquatic life.

hazard

Long-term (chronic) aquatic : Very toxic to aquatic life with long lasting effects.

hazard

Persistence and degradability

Components:

No data available Bioaccumulative potential

Components:

PETROLEUM DISTILLATES:

Partition coefficient: n-: log Pow: Expected > 7

octanol/water

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological : No data available

information

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Control Order (CCO) : Not applicable

Priority Chemical List (PCL) : Not applicable

Other international regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : Not in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information: 000000272132

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H360F May damage fertility.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-

800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit P-Statement : Precautionary Statement



Parts Plus® SAE 0W-20 Synthetic Motor Oil

Version: 4.0 Revision Date: 02/26/2020 Print Date: 03/17/2020

PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CEATOX

Assistance Center of the Institute of Toxicology Children's Hospital Clinic, Faculty of Medicine University of São Paulo.

BR OEL: Occupational Exposure Limit (Brazil)
UY OEL: Occupational Exposure Limit (Uruguay)
PY OEL: Occupational Exposure Limit (Paraguay)