

Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0	Revision Date:	12/04/2019	Print Date: 03/17/2020
SECTION 1. PRODUCT AND	COMPANY IDENTI	FICATION	
<b>Product identifier</b> Trade name		us® HIGH PERFORMANCE SAE 5W-2 ETIC BLEND vil	20
Product code	: 791497		
Recommended use	: Motor Oil	or mixture and uses advised against	
Details of the supplier o sheet Valvoline LLC	if the safety data	Emergency telephone number +1-800-VALVOLINE (+1-800-825-86	654)
100 Valvoline Way Lexington, KY 40509 United States of America		Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information	
1-800-TEAMVAL (1-800-	552-06231	1-800-TEAMVAL (1-800-832-6825)	
SDS@valvoline.com			

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Not a hazardous substance or mixture. **GHS label elements** Not a hazardous substance or mixture.

### Other hazards which do not result in classification

No information available.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
PETROLEUM DISTILLATES		Not a hazardous substance or mixture.	>= 50.00 - < 70.00



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0	Revision Date: 12/04/2019		Print Date: 03/17/2020
PETROLEUM DISTILLATES	64742-54-7	Asp. Tox. 1; H304	>= 20.00 - < 30.00
PETROLEUM DISTILLATES	64742-55-8	Asp. Tox. 1; H304	>= 1.00 - < 10.00
DISTILLATES (PETROLEUM	) 64742-65-0	Asp. Tox. 1; H304	>= 1.00 - < 10.00

SECTION 4. FIRST AID MEASURES			
General advice :	No hazards which require special first aid measures.		
If inhaled :	If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.		
In case of skin contact :	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.		
In case of eye contact :	Remove contact lenses. Protect unharmed eye.		
If swallowed :	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.		
Most important symptoms : and effects, both acute and delayed	No symptoms known or expected.		
Notes to physician :	No hazards which require special first aid measures.		

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0	Revision Date: 12/04/2019	Print Date: 03/17/2020
	Water spray Foam Carbon dioxide (CO2) Dry chemical	
Specific hazards during firefighting	<ul> <li>Do not allow run-off from fire fighting to enter drains of courses.</li> <li>If product is heated above its flash point it will product sufficient to support combustion. Vapors are heavier and may travel along the ground and be ignited by he lights, other flames and ignition sources at locations is point of release.</li> </ul>	e vapors than air eat, pilot
Hazardous combustion products	: carbon dioxide and carbon monoxide Hydrocarbons	
Specific extinguishing methods	: Standard procedure for chemical fires.	
	Product is compatible with standard fire-fighting ager	nts.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing app	oaratus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Comply with all applicable federal, state, and local regulations.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Normal measures for preventive fire protection.
Advice on safe handling	: Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Materials to avoid	: No materials to be especially mentioned.



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0

Revision Date: 12/04/2019

Print Date: 03/17/2020

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters CAS-No. Value type Control Basis Components (Form of parameters / exposure) Permissible concentration PETROLEUM DISTILLATES L-8/40 64742-58-1 0.2 mg/m3 **VE OEL** TWA 5 mg/m3 CR OEL PETROLEUM DISTILLATES CMP (Mist) 5 mg/m3AR OEL Mist CMP - CPT 10 mg/m3 AR OEL (Mist) Mist TWA (Mist) 5 mg/m3 PE OEL Mist STEL (Mist) 10 mg/m3 PE OEL Mist L-8/40 (Mist) 5 mg/m3 VE OEL Mist LB (Mist) 10 mg/m3 VE OEL Mist CPT (Mist) 5 mg/m3 PA OEL Mist CCT (Mist) 10 mg/m3 PA OEL Mist TWA (Mist, 5 mg/m3 CR OEL inhalable) Mist, inhalable STEL (Mist) 10 mg/m3 CR OEL Mist **Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local

 Personal protective equipment
 Respiratory protection

 Respiratory protection
 :

Eye protection	:	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection	:	Wear as appropriate: Safety shoes
Hygiene measures	:	General industrial hygiene practice.



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0

Revision Date: 12/04/2019

Print Date: 03/17/2020

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 199 °C
		Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	6 %(V) Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	1 %(V) Calculated Explosive Limit
Vapour pressure	:	0.0012 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8620 g/cm3 (15.56 °C)
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Decomposition temperature	:	No data available



### SAFETY DATA SHEET Parts Plus® HIGH PERFORMANCE SAE 5W-20

SYNTHETIC BLEND Motor Oil

Version: 6.0	Revision Date: 12/04/2019	Print Date: 03/17/2020
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: 50 mm2/s ( 40 °C)	
Oxidizing properties	: No data available	

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Not classified based on available information.

PETROLEUM DISTILLATES:	
Acute oral toxicity	: LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg
, , , , , , , , , , , , , , , , , , ,	

DISTILLATES (PETROLEUM):		
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity		LD50 (Rabbit): > 5,000 mg/kg
	·	



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0

Revision Date: 12/04/2019

Print Date: 03/17/2020

Skin corrosion/irritation

Not classified based on available information.

Components:

PETROLEUM DISTILLATES: Result: Slight, transient irritation

PETROLEUM DISTILLATES: Result: Slight, transient irritation

PETROLEUM DISTILLATES: Result: Slight, transient irritation

DISTILLATES (PETROLEUM): Result: Slight, transient irritation

Serious eye damage/eye irritation Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

<u>Components:</u> PETROLEUM DISTILLATES: Result: No eye irritation

PETROLEUM DISTILLATES: Result: No eye irritation

PETROLEUM DISTILLATES: Result: Slight, transient irritation

DISTILLATES (PETROLEUM): Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0	Revision Date: 12/04/2019	Print Date: 03/17/2020				
<b>Carcinogenicity</b> Not classified based on available information.						
<u>Components:</u> PETROLEUM DISTILLATES	<u>Components:</u> PETROLEUM DISTILLATES:					
Carcinogenicity - Assessment	: Classified based on DMSO extract content < 3 (EC) 1272/2008, Annex VI, Part 3, Note L)	% (Regulation				
PETROLEUM DISTILLATES	S:					
Carcinogenicity - Assessment	: Classified based on DMSO extract content < 3 (EC) 1272/2008, Annex VI, Part 3, Note L)	% (Regulation				
<b>Reproductive toxicity</b> Not classified based on avai	Reproductive toxicity Not classified based on available information.					
<b>STOT - single exposure</b> Not classified based on available information.						
<b>STOT - repeated exposure</b> Not classified based on available information. <b>Aspiration toxicity</b> Not classified based on available information.						
Product: No aspiration toxicity classif	ication					
<u>Components:</u> PETROLEUM DISTILLATES	S:					
No aspiration toxicity classification						
PETROLEUM DISTILLATES: May be fatal if swallowed and enters airways.						
PETROLEUM DISTILLATES: May be fatal if swallowed and enters airways.						
DISTILLATES (PETROLEU May be fatal if swallowed an						

### **Further information**

Product: Remarks: No data available



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0

Revision Date: 12/04/2019

Print Date: 03/17/2020

### **SECTION 12. ECOLOGICAL INFORMATION**

Ecotoxicity <u>Components:</u> PETROLEUM DISTILLATES:		
Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Aquatic invertebrates): 10 mg/l
PETROLEUM DISTILLATES:		
Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Aquatic invertebrates): 10 mg/l
No data available <b>Persistence and degradabilit</b> <u>Components:</u> No data available <b>Bioaccumulative potential</b> <u>Components:</u> PETROLEUM DISTILLATES:	у	
Partition coefficient: n- octanol/water	•	log Pow: Expected > 7



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0

. . .

Revision Date: 12/04/2019

Print Date: 03/17/2020

No data available	
Mobility in soil	
Components:	
No data available	
Other adverse effects	
No data available	
Product:	
Additional ecological	: No data available
information	

**Components:** 

### SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Contaminated packaging : Empty remaining contents.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### **SECTION 15. REGULATORY INFORMATION**

# Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Control Order (CCO)

: Not applicable

Priority Chemical List (PCL)

: Not applicable

#### Other international regulations



### SAFETY DATA SHEET Parts Plus® HIGH PERFORMANCE SAE 5W-20

SYNTHETIC BLEND Motor Oil

Version: 6.0	Revision Date: 12/04/2019	Print Date: 03/17/2020
The components of th DSL	is product are reported in the following inventories: : All components of this product are on the Canadia	In DSL
AICS	: On the inventory, or in compliance with the inventor	ory
KECI	: On the inventory, or in compliance with the inventor	ory
PICCS	: On the inventory, or in compliance with the inventor	ory
TCSI	: Not in compliance with the inventory	
TSCA	: On TSCA Inventory	

#### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

### SECTION 16. OTHER INFORMATION

### Further information

Internal information : R0366793

### Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :



Parts Plus® HIGH PERFORMANCE SAE 5W-20 SYNTHETIC BLEND Motor Oil

Version: 6.0	Revision Date: 12/04/2019	Print Date: 03/17/2020
BEI : Biological Expo CAS : Chemical Abst CMR : Carcinogenic, FG : Food grade GHS : Globally Harm H-statement : Hazard IATA : International A IATA-DGR : Dangerd ICAO : International A ICAO-TI (ICAO) : Te IMDG : International ISO : International O IogPow : octanol-wat LCxx : Lethal Concer LDxx : Lethal Concer LDxx : Lethal Dose, f ICXx : Inhibitory Cond Ecxx : Effective Cond N.O.S.: Not Otherwis OECD : Organization OEL : Occupational B P-Statement : Precat PBT : Persistent , Bid PPE : Personal Prote STEL : Short-term ex STOT : Specific Targ TLV : Threshold Limi TWA : Time-weighted	tracts Service (Division of the American Chemical So Mutagenic or Toxic for Reproduction honized System of Classification and Labeling of Che d Statement Air Transport Association. Dus Goods Regulation by the "International Air Transport civil Aviation Organization echnical Instructions by the "International Civil Aviatio Maritime Code for Dangerous Goods rganization for Standardization her partition coefficient intration, for xx percent of test population for xx percent of test population for xx percent of test population for xx of a substance centration for xx of a substance centration of xx se Specified in for Economic Co-operation and Development Exposure Limit utionary Statement baccumulative and Toxic ective Equipment coposure limit get Organ Toxicity it Value d average int and Very Bioaccumulative	pociety). emicals. port Association" (IATA).
	•	

CEATOX

Assistance Center of the Institute of Toxicology Children's Hospital Clinic, Faculty of Medicine University of São Paulo.

BR OEL : Occupational Exposure Limit (Brazil)

UY OEL : Occupational Exposure Limit (Uruguay) PY OEL : Occupational Exposure Limit (Paraguay)