| <b>Valvoline</b>                | Page: 1                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name : Parts Plus® SAE 80W-90

Gear Oil

Details of the supplier of the safety data

sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509

United States of America (USA)

1-800-TEAMVAL

**Emergency telephone number** 

+1-800-VALVOLINE (+1-800-825-8654)

**Regulatory Information Number** 

1-800-TEAMVAL

Product Information 1-800-TEAMVAL

SDS@valvoline.com

# **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Skin sensitisation : Category 1

Acute aquatic toxicity : Category 3

Chronic aquatic toxicity : Category 3

**GHS** label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:** 

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water. P333 + P313 If skin irritation or rash occurs: Get medical

| Valvoline                       | Page: 2                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

# Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

# Other hazards which do not result in classification

No information available.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components** 

| Chemical name  | CAS-No.    | Classification   | Concentration (%) |
|--|------------|--|-------------------|
| ORGANIC COMPOUND   | 68937-96-2 | 3; H316 Skin Sens. 1B; H317 Aquatic Acute 3; H402 Aquatic Chronic 3; H412                                      | >= 1.00 - < 10.00 |
| React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) |            | Flam. Liq. 4; H227 Acute Tox. 4; H302 1; H318 Skin Sens. 1; H317 Aquatic Acute 2; H401 Aquatic Chronic 2; H411 | >= 0.10 - < 1.00  |
| AMINE  | 112-90-3   | Acute Tox. 4; H302  1B; H314  1; H318  STOT RE 2; H373  Asp. Tox. 1; H304                                      | >= 0.10 - < 1.00  |

| Valvoline                       | Page: 3                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| DD2276                          |                           |
| PP3376                          |                           |

| Aquatic Acute 1; H400<br>Aquatic Chronic 1;<br>H410 |  |
|---|--|
|   |  |

# **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: May cause an allergic skin reaction.

Causes mild skin irritation.

May cause an allergic skin reaction. No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

# **SECTION 5. FIREFIGHTING MEASURES**

| Valvoline                       | Page: 4                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons Sulphur oxides

Specific extinguishing

methods

: Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Product is compatible with standard fire-fighting agents.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

Environmental precautions : Pr

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

# **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

| Valvoline                       | Page: 5                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

used.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components               | CAS-No.    | Value type    | Control         | Basis  |
|--------------------------|------------|---------------|-----------------|--------|
|                          |            | (Form of      | parameters /    |        |
|                          |            | exposure)     | Permissible     |        |
|                          |            |               | concentration   |        |
| Distillates (petroleum), | 64742-47-8 | CMP (Mist)    | 5 mg/m3         | AR OEL |
| hydrotreated middle      |            |               | Mist            |        |
|                          |            | CMP - CPT     | 10 mg/m3        | AR OEL |
|                          |            | (Mist)        | Mist            |        |
|                          |            | TWA (Mist)    | 5 mg/m3         | PE OEL |
|                          |            |               | Mist            |        |
|                          |            | STEL (Mist)   | 10 mg/m3        | PE OEL |
|                          |            |               | Mist            |        |
|                          |            | L-8/40 (Mist) | 5 mg/m3         | VE OEL |
|                          |            |               | Mist            |        |
|                          |            | LB (Mist)     | 10 mg/m3        | VE OEL |
|                          |            |               | Mist            |        |
|                          |            | CPT (Mist)    | 5 mg/m3         | PA OEL |
|                          |            |               | Mist            |        |
|                          |            | CCT (Mist)    | 10 mg/m3        | PA OEL |
|                          |            |               | Mist            |        |
|                          |            | TWA (Mist,    | 5 mg/m3         | CR OEL |
|                          |            | inhalable)    | Mist, inhalable |        |
|                          |            | STEL (Mist)   | 10 mg/m3        | CR OEL |
|                          |            |               | Mist            |        |
|                          |            | TLV-TWA       | 200 mg/m3       | DO OEL |

**Engineering measures** 

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection Respiratory protection is not required under normal conditions

| Valvoline.                      | Page: 6                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

of use.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear.

Hygiene measures : Wash hands before breaks and at the end of workday.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 218.3 °C (1013.333 hPa)

Flash point : > 222 °CMethod: Cleveland open cup

Evaporation rate : > 1

Ethyl Ether

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : < 0.1000000 mmHg

Relative vapour density : > 1AIR=1

Relative density : 0.89 (60.00 °F)

| Valvoline                       | Page: 7                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Density : 0.8916 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 146 mm2/s (40 °C)

Oxidizing properties : No data available

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: carbon dioxide and carbon monoxide

Sodium oxides

# **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Acute toxicity**

Not classified based on available information.

#### Components:

ORGANIC COMPOUND:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: Not classified as acutely toxic by ingestion under

GHS.

| Valvoline,                      | Page: 8                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Acute oral toxicity : LD50 (Rat): ca. 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The component/mixture is classified as acute

oral toxicity, category 4.

#### AMINE:

Acute oral toxicity : LD50 (Rat): 1,950 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

# Skin corrosion/irritation

Not classified based on available information.

Causes mild skin irritation.

#### Product:

Remarks: May cause skin irritation in susceptible persons.

# Components:

ORGANIC COMPOUND:

Result: Mild skin irritation

#### AMINE:

Result: Corrosive to skin

# Serious eye damage/eye irritation

Not classified based on available information.

# Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Remarks: Unlikely to cause eye irritation or injury.

# Components:

ORGANIC COMPOUND:

Result: Slight, transient irritation

| Valvoline                       | Page: 9                   |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Result: Corrosive

AMINE:

Result: Corrosive

# Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Skin sensitisation: Not classified based on available information.

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

# **Components:**

#### **ORGANIC COMPOUND:**

Test Type: Maximisation Test

Species: Guinea pig

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 406

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Test Type: Local lymph node assay

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

#### Germ cell mutagenicity

Not classified based on available information.

# Components:

# ORGANIC COMPOUND:

Genotoxicity in vitro : Test Type: in vitro assay

Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Mouse Cell type: Bone marrow

Method: OECD Test Guideline 474

Result: negative

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

| Valvoline                       | Page: 10                  |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Not classified based on available information.

# STOT - repeated exposure

Not classified based on available information.

#### Components:

AMINE:

Target Organs: Gastro-intestinal system, Liver, Immune system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated

exposure, category 2.

# **Aspiration toxicity**

Not classified based on available information.

#### Product:

No aspiration toxicity classification

#### **Components:**

AMINE:

May be fatal if swallowed and enters airways.

# **Further information**

**Product:** 

Remarks: No data available

# **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

#### Components:

Toxicity to fish

ORGANIC COMPOUND:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene

oxide and amines, C12-14-alkyl (branched):

: LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Water flea (Daphnia magna)): ca. 91.4 mg/l

Exposure time: 48 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 202

| Valvoline                       | Page: 11                  |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 15

mg/l

End point: Growth inhibition Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.3

ma/l

End point: Growth inhibition Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity) : NOEC (Water flea (Daphnia magna)): 0.12 mg/l

Exposure time: 21 d

End point: Reproduction Test Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

AMINE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0.11 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Water flea (Daphnia magna)): 0.011 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 0.083 mg/l

Exposure time: 72 h

Remarks: Information given is based on data obtained from

similar substances.

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.01

mg/l

Exposure time: 96 h

M-Factor (Acute aquatic

toxicity)

: 10

M-Factor (Chronic aquatic

toxicity)

: 10

No data available

Persistence and degradability

**Components:** 

ORGANIC COMPOUND:

| Valvoline                       | Page: 12                  |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 13 % Exposure time: 28 d

Method: OECD Test Guideline 301B

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 7.4 % Exposure time: 28 d

Method: Modified Sturm Test

AMINE:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 44 % Exposure time: 28 d

No data available

Bioaccumulative potential

Components:

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Partition coefficient: n- : Remarks: No data available

octanol/water

AMINE:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): > 500

Partition coefficient: n-

octanol/water

: log Pow: Estimated > 4

No data available **Mobility in soil** 

**Components:** 

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

**Components:** 

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

| Valvoline.                      | Page: 13                  |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

# **SECTION 14. TRANSPORT INFORMATION**

# International transport regulations

#### **REGULATION**

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD | SUBSIDIARY | PACKING | MARINE      |
|-----------|----------------------|---------|------------|---------|-------------|
|           |                      | CLASS   | HAZARDS    | GROUP   | POLLUTANT / |
|           |                      |         |            |         | LTD. QTY.   |

#### **INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

| Not dangerous goods |  |
|---------------------|--|
|                     |  |

#### **INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

| Not dangerous goods |  |
|---------------------|--|
|                     |  |

### INTERNATIONAL MARITIME DANGEROUS GOODS

| INTERNATIONAL INVALITME DAMOEROOD GOODS |  |  |  |  |
|---|--|--|--|--|
| Not dangerous goods                     |  |  |  |  |
|   |  |  |  |  |

# UN\_DG

| Not dangerous goods |  |
|---------------------|--|
|                     |  |

# \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

| Marine pollutant | no |
|------------------|----|
|                  |    |

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15. REGULATORY INFORMATION**

# Safety, health and environmental regulations/legislation specific for the substance or mixture

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

Chemical Control Order (CCO) : Not applicable

| Valvoline                       | Page: 14                  |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Priority Chemical List (PCL) : Not applicable

Hazardous Substance Act B.E. 2535 : Not applicable

Emergency Decree on Controlling the Use of Volatile : Not applicable

Substances B.E. 2533

# Other international regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

# **SECTION 16. OTHER INFORMATION**

## **Further information**

Revision Date: 06/05/2017

# **Full text of H-Statements**

| H227 | Combustible liquid.  |
|------|--|
| H302 | Harmful if swallowed.  |
| H304 | May be fatal if swallowed and enters airways.                      |
| H314 | Causes severe skin burns and eye damage.                           |
| H316 | Causes mild skin irritation.                                       |
| H317 | May cause an allergic skin reaction.                               |
| H318 | Causes serious eye damage.   |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life.  |
| H401 | Toxic to aquatic life.   |
| H402 | Harmful to aquatic life.   |
| H410 | Very toxic to aquatic life with long lasting effects.              |
| H411 | Toxic to aquatic life with long lasting effects.                   |
| H412 | Harmful to aquatic life with long lasting effects.                 |
|      |  |

| Valvoline                       | Page: 15                  |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by

Valvoline's Environmental Health and Safety Department (1-

800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

| Valvoline                       | Page: 16                  |
|---------------------------------|---------------------------|
| SAFETY DATA SHEET               | Revision Date: 06/05/2017 |
|                                 | Print Date: 3/17/2020     |
|                                 | SDS Number: R0091437      |
| Parts Plus® SAE 80W-90 Gear Oil | Version: 4.0              |
| PP3376                          |                           |

# CEATOX

Assistance Center of the Institute of Toxicology

Children's Hospital Clinic, Faculty of Medicine
University of São Paulo.

BR OEL: Occupational Exposure Limit (Brazil)
UY OEL: Occupational Exposure Limit (Uruguay)
PY OEL: Occupational Exposure Limit (Paraguay)