MSDS Number: \$4394 * * * * * Effective Date: 05/19/08 * * * * * Supercedes: 08/17/05

MSDS MATERIAL SAFETY DATA SHEET CHEMTREC: 800-424-9300 (USA)

----- 703-527-3887(Outside USA and Canada)

CANUTEC: 613-996-6666

From: Mallinckrodt Baker, Inc

222 Red School Lane

Phillipsburg, NJ 08865 NOTE: Use CHEMTREC and CANUTEC

phone numbers only in the event

Emergency Telephone Number: 908-859-2151 of a chemical emergency.

All non-emergency questions should be directed to Customer Service (1-800-582-2537) for assistance.

MALLINCKRODT

J. T. BAKER

SODIUM MOLYBDATE

1. Product Identification

Synonyms: Molybdic Acid, Disodium Salt, Dihydrate; Disodium molybdate dihydrate; sodium molybdate

dihydrate

CAS No.: 7631-95-0 (Anhydrous); 10102-40-6 (Dihydrate)

Molecular Weight: 241.95

Chemical Formula: Na2MoO4 . 2H2O

Product Codes: J.T. Baker: 3764 Mallinckrodt: 7782

2. Composition/Information on Ingredients

| Ingredient | CAS No | Percent | Hazardous |
|------------------|-----------|-----------|-----------|
| | | | |
| Sodium Molybdate | 7631-95-0 | 99 - 100% | Yes |

3. Hazards Identification

Emergency Overview

WARNING! HARMFUL IF INHALED. MAY BE HARMFUL IF SWALLOWED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 2 - Moderate Flammability Rating: 0 - None Reactivity Rating: 1 - Slight Contact Rating: 2 - Moderate Lab Protective Equip: GOGGLES; LAB COAT; VENT HOOD; PROPER GLOVES

Storage Color Code: Green (General Storage)

Potential Health Effects

Inhalation:

Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. Can be route for absorption of soluble salts of molybdenum.

Ingestion:

Moderately toxic because of solubility. Large doses cause severe distress; cramping, vomiting, and hypertension.

Skin Contact:

Can be irritating to wet skin causing a rash which is difficult to heal.

Eve Contact:

Irritant to soft tissues. Acts as a sensitizer.

Chronic Exposure:

No specific information found. Molybdenum is rapidly excreted from the body. Persons exposed for long periods suffer from anemia.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems or impaired respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact:

Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Not considered to be a fire hazard.

Explosion:

Not considered to be an explosion hazard.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal.

7. Handling and Storage

Keep in a tightly closed container. Protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL):

5 mg/m3 for soluble molybdenum compounds as Mo

15 mg/m3 total dust, for insoluble molybdenum compounds as Mo

-ACGIH Threshold Limit Value (TLV):

Molybdenum, metal and insoluble compounds, inhalable fraction, as Mo: 10 mg/m3

Molybdenum, metal and insoluble compounds, respirable fraction, as Mo: 3 mg/m3

Molybdenum, soluble compounds, respirable fraction, as Mo: 0.5 mg/m3, A3 - Confirmed animal carcinogen with unknown relevance to humans

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a full facepiece particulate respirator (NIOSH type N100 filters) may be worn for up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids. glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Small white scales or flakes.

Odor:

Odorless.

Solubility:

84 g/100 g water @ 100C (212F)

Specific Gravity:

3.28 @ 18C (64.4F)

pH:

No information found.

% Volatiles by volume @ 21C (70F):

0

Boiling Point:

Not applicable.

Melting Point:

687C (1269F)

Vapor Density (Air=1):

No information found.

Vapor Pressure (mm Hg):

No information found.

Evaporation Rate (BuAc=1):

No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Toxic metal fumes may form when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Incompatible with alkali metals, most common metals and oxidizing agents. Explodes on contact with molten magnesium. Violent reaction with interhalogens (e.g., bromine pentafluoride; chlorine trifluoride). Incandescent reaction with hot sodium, potassium or lithium.

Conditions to Avoid:

Moisture, heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Hydrate: Investigated as a reproductive effector. Anhydrous: Oral rat LD50: 4 gm/kg; Inhalation rat LC50: > 2080 mg/m3/4H. Investigated as a mutagen, reproductive effector.

| \Cancer Lists\ | | Carcinogen | |
|------------------------------|-------|----------------|---------------|
| Ingredient | Known | Anticipated | IARC Category |
| Sodium Molybdate (7631-95-0) | No | No | None |

12. Ecological Information

Environmental Fate:

No information found.

Environmental Toxicity:

No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

15. Regulatory Information

| Ingredient | | TSCA | EC | Japan | Australia |
|--|---------------------------------|--------------------|--------------------------|--------------------|------------|
| Sodium Molybdate (7631-95-0) | | | | | Yes |
| \Chemical Inventory Status - P | art 2\ | | | | |
| Ingredient | | | DSL | | Phil. |
| Sodium Molybdate (7631-95-0) | | | | | Yes |
| \Federal, State & Internationa | | | | | |
| Ingnodiant | | | | | A 313 |
| Ingredient | | | | | |
| Ingredient Sodium Molybdate (7631-95-0) | | | | | |
| | No | No No ions - | No No | 2\ | No |
| Sodium Molybdate (7631-95-0) | No No l Regulat: CERCI | No No ions - | Part : -RCRA 261.3 | 2\ T 3 8 | No SCA- |

Australian Hazchem Code: None allocated.

Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 2 Flammability: 0 Reactivity: 0

Label Hazard Warning:

WARNING! HARMFUL IF INHALED. MAY BE HARMFUL IF SWALLOWED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

Label Precautions:

Avoid contact with eyes, skin and clothing.

Avoid breathing dust.

Keep container closed.

Heat will contribute to instability.

Use only with adequate ventilation.

Wash thoroughly after handling.

Label First Aid:

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention.

Product Use:

Laboratory Reagent.

| _ | | T 0 | . • |
|---|---------|--------|--------|
| К | evision | Inform | ation: |

No Changes. **Disclaimer:**

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Environmental Health & Safety Phone Number: (314) 654-1600 (U.S.A.)